

5 OUTBOARD
YEARS
warranty
FOR LEISURE USE ONLY
Subject to terms and conditions
see your Dealer for more
information



OUTBOARD MOTORS



FOLLOW US ON
SELVA MARINE



5 OUTBOARD
YEARS
warranty

FOR LEISURE USE ONLY
Subject to terms and conditions
see your Dealer for more
information

Selva Marine engines come with a five-year limited warranty. Certain conditions and exclusions apply including professional and commercial use.



OUTBOARD MOTORS

**43 Powerful companions
of navigation**

43 MODELS

3 RANGE

POWER FROM 2,5HP TO 2X250HP

5 YEARS WARRANTY

Come closer look...

There are a number of boating solutions waiting for you. Whether you prefer the elegance and relaxation of a lake, speed with open sea adventures or the thrill of powering from one island to another, **Selva** will accompany you providing power, control and great service. The wonderful world

of powerboating is now affordable and ready. Reach inlets with your friends, enjoy a beautiful sunset with your partner, or amaze everyone with landscapes that will remain in their hearts together with a lifetime passion for the sea. This is the **Selva** world, a constant surprise to enjoy. Join it now.



6 MODELS FROM 60HP TO 2X150 HP IN 10 VERSIONS

Burning acceleration and low consumption are the main characteristics of the Selva 4-stroke range for leisure, professional or commercial use. So they are specially developed for the most demanding people. The advanced electronic system controls all the engine's functions in the best way and gives breath-taking performance and fuel economy.



p 04



32 MODELS FROM 4HP TO 2X250HP IN 96 VERSIONS

This Selva Marine range has a strong and distinctive personality that operates in total respect of nature. The use of sophisticated technologies, their compactness, elegant and innovative design make these outboard motors a range that does not go unnoticed in the pleasure boating sector.



p 08



5 MODELS FROM 15HP TO 80HP IN 7 VERSIONS

Agile and easy to handle, Selva 2-strokes allow for strong and safe navigation. Lightweight and powerful, with simple and robust controls to operate, these motors are reliable and faithful workhorses that adapt well for those who use the sea for their professional or commercial activities.



p 22



Dorado E.F.I.
60 XSR

Murena E.F.I.
70 XSR

TECHNICAL CHARACTERISTICS



	<i>Dorado</i>	<i>Murena</i>	<i>Marlin</i>
Power (hp)	60XSR EFI	70XSR EFI	100XSR EFI
Power (kW)	44,1	51,5	73,6
Max. R.P.M.	5000 - 6000	5300-6300	5000-6000
Motor type	4 Stroke SOHC	4 Stroke SOHC-16V	4 Stroke DOHC-16V
Swept volume c.c.	996		1596
Bore x Stroke (mm)	65x75		79x81,4
N° Cylinders	4 in-line		
Induction	Electronic Injection		
Choke	Automatic		
Fuel	Petrol (for specifications see the user manual)		
Fuel tank (L)	Separate 23		Not provided
Lubrication	Forced (oil sump)		
Ignition	T.C.I./Computer		
Ignition timing	Electronic		
Starting	Electric		
Alternator	Standard 12V/200W with regulator		Standard 12V/300W with regulator
Cooling	Water cooled with pump-forced circulation		
Exhaust	Underwater through propeller		
Steering system	Remote with remote control box		
Type of remote control box provided (for the version with remote control box)	Single remote control box with safety switch		
Trim adjustment	Power Trim/Tilt		
Gears	Mechanical F-N-R		
Transmission Ratio	13/24	12/28	11/25
Available shaft versions	L	L-XL	L-XL
Standard propeller type	3-bladed with built-in spring drive		
Weight basic version (kg)	111	119	170

Marlin E.F.I.
100 XSR

Some models may not be available in all countries or they may have different, non-standard horsepower depending on the different national legislative requirements. (For further details see the current price list.)
The data contained in this table are to be considered as approximate and **Selva Marine** reserves the right to modify the technical characteristics, materials, construction, weights etc. without any forewarning or obligations.



Swordfish
115 XSR



Killer Whale E.F.I.
150 XSR

TECHNICAL CHARACTERISTICS



	Swordfish	Killer Whale	Counter rotating pair Killer Whale
Power (hp)	115 XS ^R EFI	150 XS ^R EFI	2 x 150 XS ^R EFI
Power (kW)	84,6	110,3	2 x 110,3
Max. R.P.M.	5300/6300	5000/6000	
Motor type	4 Stroke DOHC - 16V		
Swept volume c.c.	1832	2670	2 x 2670
Bore x Stroke (mm)	81 x 88,9	94x96,2	2 x 94x96,2
N° Cylinders	4 on line		2 x 4 on line
Induction	Electronic Injection		
Choke	Automatic		
Fuel	Petrol (for specifications see the user manual)		
Fuel tank (L)	Not provided		
Lubrication	Forced (oil sump)		
Ignition	T.C.I./Computer		
Ignition timing	Electronic		
Starting	Electric		
Alternator	Standard 12V / 420W with regulator		Standard 2 x 12V/420W with regulator
Cooling	Water cooled with pump-forced circulation		
Exhaust	Underwater through propeller		
Steering system	Remote with remote control box		
Type of remote control box provided (for the version with remote control box)	Single remote control box with safety switch	Single binnacle lever with safety switch	Two lever binnacle with safety switch
Trim adjustment	Power Trim/Tilt		
Gears	Mechanical F-N-R		
Transmission Ratio	13/28	14/28	
Available shaft versions	L - XL.		XL.
Standard propeller type	3-bladed with built-in spring drive		3-bladed with built-in spring drive, incorporated silent-block counter rotating pair
Weight basic version (kg)	175	216	2 x 216

Killer Whale E.F.I.
2 X 150 XSR

COUNTER ROTATING PAIR

Some models may not be available in all countries, or they may have different, non-standard horse powers. Depending on the different national legislative requirements. (For further details see the current price list).
The data contained in this table are to be considered as approximate and **Selva Marine** reserves the right to modify the technical characteristics, materials, construction, weights, etc. without any forewarning or obligations.



NEW



Guppy
2,5



Sea Bass
4/5



Sea Bass
6

TECHNICAL CHARACTERISTICS



	Guppy	Sea Bass			Oyster
Power (hp)	2,5	4	5	6	6
Power (kW)	1,84	2,9	3,7	4,4	4,4
Max. R.P.M.	4500-5500	5000 / 5500			
Motor type	4 Stroke OHV	4 Stroke SOHC			
Swept volume c.c.	87	118			135
Bore x Stroke (mm)	54 x 38	56 x 48			57 x 53
N° Cylinders		1			
Induction		1 carburettor			
Choke		Manual			
Fuel		Petrol (for specifications see the user manual)			
Fuel tank (L)	Integrated 0,9	Integrated 1,6 with connection for external tank			
Lubrication	Forced	Automatic oil injection into fuel			Forced with mechanical lobe-pump
Ignition		C.D.I. Digital			
Ignition timing		Electronic			
Starting		Manual			
Alternator	Not available	Optional 12V/70W with rectifier			
Cooling		Water cooled with pump-forced circulation			
Exhaust	Underwater	Underwater through propeller			
Steering system		Tiller bar steering with twist grip throttle control and steering friction adjustment			
Trim adjustment	Manual (4 pos)	Manual (4 pos) with trim for navigation in shallow waters			
Gears	Mechanical A-F + 360° shaft rotation	Mechanical F-N-R + 360° shaft rotation			
Transmission ratio	13/28	13/30			
Available shaft versions	C.	C. - L.			
Standard propeller type	3-bladed	3-bladed with built-in spring drive			
Weight basic version (Kg)	13,5	23			27

Oyster
6

Some models may not be available in all countries, or they may have different, non-standard horse powers. Depending on the different national legislative requirements. (For further details consult the current price list).
The data contained in this table are to be considered as approximate and **Selva Marine** reserves the right to modify the technical characteristics, materials, construction, weights, etc. without any forewarning or obligations.



Oyster B.F.

6



Oyster B.F. *Sail*

6



Black Bass

8

TECHNICAL CHARACTERISTICS



Black Bass B.F.

8

	Oyster Big Foot	Oyster Big Foot Sail	Black Bass	Black Bass Big Foot
Power (hp)	6	6	8	8
Power (kW)	4,4	4,4	5,9	5,9
Max. R.P.M.	5500 / 6000			
Motor type	4 Stroke SOHC			
Swept volume c.c.	135		165	
Bore x Stroke (mm)	57 x 53		63 x 53	
N° Cylinders	1			
Induction	1 carburettor			
Choke	Manual or Electrical		Manual	Manual or Electrical
Fuel	Petrol (for specifications see the user manual)			
Fuel tank (L)	Separate 12		Separate 12 or built-in 1.8	Separate 12
Lubrication	Forced with mechanical lobe-pump			
Ignition	C.D.I. Digital			
Ignition timing	Electronic			
Starting	Manual or Electric also with integrated ISB battery (not available in versions with built-in tank)			
Alternator	Optional 12V/70W with rectifier on Manual start version Standard 12V/70W with rectifier on Electric start version			
Cooling	Water cooled with pump-forced circulation			
Exhaust	Underwater through propeller			
Steering system	Tiller bar steering with twist grip throttle control and steering friction adjustment or remote with remote control box		Tiller bar steering with twist grip throttle control and steering friction adjustment	Tiller bar steering with twist grip throttle control and steering friction adjustment or remote with remote control box
Type of remote control box provided (for the version with remote control box)	Single lever with safety switch		Not applicable	Single lever with safety switch
Trim adjustment	Manual (4 pos) with trim for navigation in shallow waters			
Gears	Mechanical F-N-R		Mechanical F-N-R + 3 60° shaft rotation	Mechanical F-N-R
Transmission Ratio	13/27		13/30	13/27
Available shaft versions	C. - L.	XL.	C. - L.	
Standard propeller type	3-bladed with built-in spring drive			
Weight basic version (kg)	30,5	32	27	30,5

Some models may not be available in all countries, or they may have different, non-standard horse powers. Depending on the different national legislative requirements. (For further details consult the current price list).
The data contained in this table are to be considered as approximate and **Selva Marine** reserves the right to modify the technical characteristics, materials, construction, weights, etc. without any forewarning or obligations.



Black Bass B.F. Sail

8



Ray

8



Piranha

9,9

TECHNICAL CHARACTERISTICS



	Black Bass Big Foot Sail	Ray	Piranha	Piranha Sail
Power (Hp)	8	8	9,9	9,9
Power (kW)	5,9	5,9	7,3	7,3
Max. R.P.M.	5500 / 6000	5000/6000	5500 / 6000	
Motor type	4 Stroke SOHC			
Swept volume c.c.	165	197	181	
Bore x Stroke (mm)	63 x 53	56x43	66 x 53	
N° Cylinders	1	2 in-line	1	
Induction	1 carburettor			
Choke	Manual or Electrical	Manual	Manual or Electrical	
Fuel	Petrol (for specifications see the user manual)			
Fuel tank (L)	Separate 12			
Lubrication	Forced with mechanical lobe-pump	Forced (oil sump)	Forced with mechanical lobe-pump	
Ignition	C.D.I. Digital	C.D.I. Micro-computer	C.D.I. Digital	
Ignition timing	Electronic			
Starting	Manual or Electrical also with integrated ISB battery	Manual	Manual or Electrical also with integrated ISB battery	
Alternator	Optional 12V/70W with rectifier on Manual start version Standard 12V/70W with rectifier on Electric start version	Standard 12V/70W (regulator optional)	Optional 12V/70W with rectifier on Manual start version Standard 12V/70W with rectifier on Electric start version	
Cooling	Water cooled with pump-forced circulation			
Exhaust	Underwater through propeller			
Steering system	Tiller bar steering with twist grip throttle control and steering friction adjustment or remote with remote control box	Tiller bar steering with twist grip throttle control and steering friction adjustment	Tiller bar steering with twist grip throttle control and steering friction adjustment	
Type of remote control box provided (for the version with remote control box)	Single lever with safety switch	Accessory, Single lever	Single lever with safety switch	
Trim adjustment	Manual (4 pos) with trim for navigation in shallow waters			
Gears	Mechanical F-N-R			
Transmission Ratio	13/27			
Available shaft versions	XL.	C.- L.	XL.	
Standard propeller type	3-bladed with built-in spring drive			
Weight basic version (kg)	32	39,9	30,5	32

Piranha Sail

9,9

Some models may not be available in all countries, or they may have different, non-standard horse powers. Depending on the different national legislative requirements. (For further details consult the current price list).
The data contained in this table are to be considered as approximate and **Selva Marine** reserves the right to modify the technical characteristics, materials, construction, weights, etc. without any forewarning or obligations.



Pike

9,9



Wahoo

15



Wahoo

20

TECHNICAL CHARACTERISTICS



	Pike	Wahoo	Kingfish
Power (hp)	9,9	15	25
Power (kW)	7,3	11	14,7
Max. R.P.M.	5000/6000		
Motor type	4 Stroke SOHC		
Swept volume c.c.	212	362	498
Bore x Stroke (mm)	56 x 43	63 x 58,1	65x75
N° Cylinders	2 in-line		
Induction	1 carburettor		
Choke	Manual	Automatic	
Fuel	Petrol (for specifications see the user manual)		
Fuel tank (L)	Separate 12		Separate 23
Lubrication	Forced (oil sump)		
Ignition	C.D.I. Micro-computer		
Ignition timing	Electronic		
Starting	Manual or Electric		
Alternator	Standard 12V/70W (regulator optional) on Manual start version Standard 12V/70W with regulator on Electric start version	Standard 12V/120W (regulator optional) on Manual start version Standard 12V/120W with regulator on Electric start version	Standard 12V/160W (regulator optional) on Manual start version Standard 12V/160W with regulator on Electric start version
Cooling	Water cooled with pump-forced circulation		
Exhaust	Underwater through propeller		
Steering system	Tiller bar steering with twist grip throttle control and steering friction adjustment or remote with remote control box according to version		
Type of remote control box provided (for the version with remote control box)	Single lever with safety switch		
Trim adjustment	Manual (4 pos) with trim for navigation in shallow waters	Manual (4 pos) with trim for navigation in shallow waters or Power Tilt depending on the version	Manual (4 pos) with trim for navigation in shallow waters or Power Tilt depending on the version
Gears	Mechanical F-N-R		
Transmission Ratio	13/27		
Available shaft versions	C. - L.		
Standard propeller type	3-bladed with built-in spring drive		
Weight basic version (kg)	39,9	51,7	77

Kingfish

25

Some models may not be available in all countries, or they may have different, non-standard horse powers. Depending on the different national legislative requirements. (For further details consult the current price list).
The data contained in this table are to be considered as approximate and **Selva Marine** reserves the right to modify the technical characteristics, materials, construction, weights, etc. without any forewarning or obligations.



Aruana E.F.I.

40



Dorado E.F.I.

50



Dorado E.F.I.

60

TECHNICAL CHARACTERISTICS



	Aruana	Dorado		Murena
Power (hp)	40 EFI	50 EFI	60 EFI	70 EFI
Power (kW)	29,4	36,8	44,1	51,5
Max. R.P.M.		5000 - 6000		5300 / 6300
Motor type		4 Stroke SOHC		4 Stroke SOHC 16V
Swept volume c.c.	747		996	
Bore x Stroke (mm)		65x75		
N° Cylinders	3 in-line		4 in-line	
Induction		Electronic Injection		
Choke		Automatic		
Fuel		Petrol (for specifications see the user manual)		
Fuel tank (L)		Separate 23		
Lubrication		Forced (oil sump)		
Ignition		T.C.I./Computer		
Ignition timing		Electronic		
Starting		Electric		
Alternator	Standard 12V/190W with regulator		Standard 12V/200W with regulator	
Cooling		Water cooled with pump-forced circulation		
Exhaust		Underwater through propeller		
Steering system	Tiller bar steering with twist grip throttle control and steering friction adjustment or remote with remote control box, depending on the version		Remote with remote control box	
Type of remote control box provided (for the version with remote control box)			Single remote control box with safety switch	
Trim adjustment	Power trim with hydraulic damper or Power Trim/Tilt depending on the version		Power Trim/Tilt	
Gears		Mechanical F-N-R		
Transmission Ratio	13/26		13/24	12/28
Available shaft versions			L.	L.-XL.
Standard propeller type		3-bladed with built-in spring drive		
Weight basic version (kg)	99		111	119

Murena E.F.I.

70

Some models may not be available in all countries, or they may have different, non-standard horse powers. Depending on the different national legislative requirements. (For further details see the current price list).
The data contained in this table are to be considered as approximate and **Selva Marine** reserves the right to modify the technical characteristics, materials, construction, weights, etc. without any forewarning or obligations.



Marlin E.F.I.
100/80XS



Swordfish
115



Killer Whale E.F.I.
150

TECHNICAL CHARACTERISTICS



	Marlin		Swordfish	Killer Whale	Counter rotating pair Killer Whale
Power (hp)	80XS EFI	100 EFI	115 EFI	150 EFI	2 x 150 EFI
Power (kW)	58,8	73,6	84,6	110,3	2 x 110,3
Max. R.P.M.	5000/6000		5300/6300	5000/6000	
Motor type	4 Stroke DOHC - 16V				
Swept volume c.c.	1596		1832	2670	2 x 2670
Bore x Stroke (mm)	79x81,4		81x88,9	94x96,2	2 x 94x96,2
N° Cylinders	4 in-line				2 x 4 in-line
Induction	Electronic Injection				
Choke	Automatic				
Fuel	Petrol (for specifications see the user manual)				
Fuel tank (L)	Not provided				
Lubrication	Forced (oil sump)				
Ignition	T.C.I./Computer				
Ignition timing	Electronic				
Starting	Electric				
Alternator	Standard 12V/300W with regulator		Standard 12V / 420W with regulator		Standard 2 x 12V/420W with regulator
Cooling	Water cooled with pump-forced circulation				
Exhaust	Underwater through propeller				
Steering system	Remote with remote control box				
Type of remote control box provided (for the version with remote control box)	Single remote control box with safety switch			Single binnacle lever with safety switch	Two lever binnacle with safety switch
Trim adjustment	Power Trim/Tilt				
Gears	Mechanical F-N-R				
Transmission Ratio	11/25		13/28		14/28
Available shaft versions	L-XL		L - XL		XL
Standard propeller type	3-bladed with built-in spring drive				3-bladed with built-in spring drive, incorporated silent-block counter rotating pair
Weight basic version (kg)	170		175	216	2 x 216

Killer Whale E.F.I.
2 X 150

COUNTER ROTATING PAIR

Some models may not be available in all countries, or they may have different, non-standard horse powers. Depending on the different national legislative requirements. (For further details see the current price list).
The data contained in this table are to be considered as approximate and **Selva Marine** reserves the right to modify the technical characteristics, materials, construction, weights, etc. without any forewarning or obligations.



Grey Whale E.F.I.
200



Fin Whale E.F.I.
225



Blue Whale E.F.I.
250

TECHNICAL CHARACTERISTICS



	Grey whale	Fin whale	Blue whale	Counter rotating pair Grey whale	Counter rotating pair Fin whale	Counter rotating pair Blue whale
Power (hp)	200 EFI	225 EFI	250 EFI	2 x 200 EFI	2 x 225 EFI	2 x 250 EFI
Power (kW)	147,1	165,5	183,9	2 x 147,1	2 x 165,5	2 x 183,9
Max. R.P.M.	5000 / 6000					
Motor type	4 stroke DOHC - 24V with VTC direct acting					
Swept volume c.c.	3352			2 x 3352		
Bore x Stroke (mm)	94 x 80,5			2 x 94x80,5		
N° Cylinders	6 a V 60°			2 x 6 a V 60°		
Induction	Electronic Injection					
Choke	Automatic					
Fuel	Petrol (for specifications see the user manual)					
Fuel tank (L)	Not provided					
Lubrication	Forced (oil sump)					
Ignition	T.C.I./Computer					
Ignition timing	Electronic					
Starting	Electric					
Alternator	Standard 12V/550W with regulator			Standard 2 x 12V/550W with regulator		
Cooling	Water cooled with pump-forced circulation					
Exhaust	Underwater through propeller					
Steering system	Remote steering system with remote control box					
Type of remote control box provided (for the version with remote control box)	Single lever binnacle or flush with safety switch			Two lever binnacle with safety switch		
Trim adjustment	Power Trim/Tilt					
Gears	Mechanical F-N-R					
Transmission Ratio	15/30					
Available shaft versions	XL.		XL - UL.		XL.	
Standard propeller type	3-bladed with built-in spring drive			3-bladed with built-in spring drive, counter rotating pair		
Weight basic version (kg)	278			2 x 278		

Grey/Fin/Blue Whale E.F.I.

2 X 200/225/250

COUNTER ROTATING PAIR

Some models may not be available in all countries, or they may have different, non-standard horse powers. Depending on the different national legislative requirements. (For further details see the current price list).

The data contained in this table are to be considered as approximate and **Selva Marine** reserves the right to modify the technical characteristics, materials, the right to modify the technical characteristics, materials, construction, weights, etc. without any forewarning or obligations.

The 4 strokes efi engines v-6 of 200, 225 and 250 hp, single or in counterrotation, are available exclusively with the package formula with the wide range of **Selva Marine** inflatable and GRP boats.



Naxos

15



Antibes

30



Madeira

50



St. Tropez

60

TECHNICAL CHARACTERISTICS



Portofino

80

	Naxos	Antibes	Madeira	St. Tropez	Portofino
Power (hp)	15	30	50	60	80
Power (kW)	11	22	36,8	44,1	58,8
Max. R.P.M.	5500		5500	5500	
Motor type			2 Stroke		
Swept volume c.c.	260	489	684	831	1025
Bore x Stroke (mm)	58 x 49	72 x 60	80 x 68	71 x 68	80 x 68
N° Cylinders	2 in-line			3 in-line	
Intake ports	4 ports, with corrected crossflow			5 ports, with corrected crossflow	
Induction	1 pump + 1 carburettor		1 pump + 2 carburettors	1 pump + 3 carburettors	
Oil/fuel mixing	Manual		Automatic Multipoint with variable ratio oil Injection		
Fuel	Petrol + Marine oil (for specifications and mix ratios, see user manual)			Petrol (for specifications see user manual)	
Fuel tank (L)	23				
Ignition	C.D.I. - Electronic capacitor discharge - fully sealed capacitor discharge for each cylinder				
Ignition timing	Automatic Electronic programmed to suit R.P.M.				
Starting	Manual			Electric	
Alternator	Optional 12V/70W with rectifier			Standard 12V/70W with rectifier	
Cooling	Water cooled with pump-forced circulation				
Exhaust	Bilateral, underwater with depression by propeller				
Steering system	Tiller bar steering with twist grip throttle control and steering friction adjustment			Remote with remote control box	
Type of remote control box provided	Accessory, Single lever			Single lever with safety switch	
Suspension	Disk silent block			Controlled compression and traction silent block	
Trim adjustment	5 positions by pin location			Power Trim/Tilt	
Gears	Mechanical F-N-R				
Transmission ratio	13 / 25		13 / 27		
Available shaft versions	C. - L.			L.	
Standard propeller type	3-bladed with build-in spring drive				
Weight basic version (Kg)	30	53	72	104	109

The 2-stroke outboard models may not be available in all countries, or they may have different, non-standard horse powers. Depending on the different national legislative requirements. (For further details consult the current price list).

The data contained in this table are to be considered as approximate and Selva Marine reserves the right to modify the technical characteristics, materials, construction, weights, etc. without any forewarning or obligations.

The 2 stroke outboard carbureted engines are not intended for installation on recreational craft within the European Union, because they have not been certified for compliance with the exhaust and noise emissions requirements of the DIRECTIVE 2013/53/EC relating to recreational craft.



Q8  Oils



www.selvamarine.com



SELVA S.p.A.

Head office and main factory:

Viale dell'Industria, 13 - 23037 Tirano (SO) - Italia

Tel. 0342-702451 - Fax 0342-705361

VAT Number IT 00050830140

Company Registration

SO n. 00050830140 - REA n. 18382